



PUMP FOR PIGGING / CHEMICAL CLEANING

Dimensions

Length(mm).....: 2400 Width(mm).....: 1200 Height(mm).....: 1300
 Weight (kg).....: 1000
 Lifting/ Transportation.....: Frame with forklift channels

Construction year

Built.....: 1996

Area of use / certification

Onshore/offshore.....: Onshore
 Power (Electrical/Diesel).....: Electrical

Flow / Pressure / Volume

Hz v Q-max measure.....: 50 Q-max (l/min).....: 3000
 Hz v P-max measure.....: 50 P-max (bar).....: 10

Connections

Inlet connection.....: 1 ea. 4" 150# RF flange
 Outlet connection.....: 1 ea. 4" 150# RF flange

Pump(s)

Pump1 (type).....: Etanorm KSB 80-250

Motor / Engine(s)

Motor1 (type).....: KSB-IEC, 380 VD 103A 50 Hz 55 Kw

Power supply

Fuse (qty).....: 1 Fuse (A).....: 125
 El.Power1.....: 380 VD (Hz).....: 50 (kW).....: 55 (A).....: 103
 Starter.....: Industri DOL D/Y, 380 V 50 Hz 55 Kw

Additional information

Equipment / Functions.....: Butterfly valve and manometer on the pressure side to control flow and pressure.
 Pump in acid-resistant material.