



PUMP FOR PIGGING / CHEMICAL CLEANING

Dimensions

Weight (kg)...... 11000

Lifting/ Transportation...... Frame with forklift channels and lifting slings.

Serial Number: K100801HU

Construction year

Built...... 2010

Area of use / certification

Pump(s)

Pump1 (type)...... MUST BE CONNECTED TO SEPERATE PUMP UNIT (PP-68B or PP-68C)

Motor / Engine(s)

Motor1 (type)..... Detroit S60 @ 500HP

Power supply

Control Panel...... 12V / 95 Ah(Control, gas/fire central)

Flow / Pressure / Volume

Additional information

Equipment / Functions...... HYDRAULIC POWER PACK
Hydraulic Tank Volume : 760 ltr

Q @ P max : 568 ltr/min @ 345 bar

MUST BE CONNECTED TO SEPERATE PUMP UNIT (PP-68B Triplex or PP-68C Centrifugal), (see separate datasheets for technical information)

Two-piece unit, where the engine and pump has to be connected.

The unit is remote-operated from pump control panel only, but can also be driven from local panel.

MOTOR SHUT DOWN IF:

- To high r.p.m on motor.
- Protective guard on pump.
- High exhaust temperature.
- Emergency stop from control room
- High coolant temperature.
- Emergency stop.
- Low oil pressure.
- Low air pressure.