



NITROGEN PUMP

Dimensions

Length(mm).....:	5490	Width(mm).....:	2445	Height(mm).....:	2970
Weight (kg).....:	14500				
Lifting/ Transportation.....:	18' Container with forklift channels and liftings.				
Certificate(s) / Serial No:.....:	NP-48 / DNV				

Construction year

Built.....: 2015

Area of use / certification

Onshore/offshore.....: Offshore
 Standard.....: Zone II, Solas 74 ch.II-2, ATEX II 3G IIA T3, 83 dBA

Flow / Pressure / Volume

Q max (SCF/H).....:	180000
Q-max - Alternative 2 (SCF/H).....:	100000
P-max (bar).....:	690
P-max Alternative 2 (bar).....:	1034

Connections

Inlet connection.....: 2 ea, 1 1/2" Acme 150
 Outlet connection.....: Out: 2" Weco Fig. 1502 male / 1" NPTF
 Return: 1 ea. 1 1/2" Acme 150

Pump / Engine

Triplex pump.....: CS&P Cryogenics ICPE-200
 Boost pump.....: CS&P Cryogenics 1,5 x 2, 5 x 6
 Cold-ends.....: CS&P 1,625" – 1,25"
 Vaporizer.....: CS&P Pot Vaporizer 180K SCFH 15000 PSI
 Motor.....: Caterpillar C-15 ATEX Petroleum, 540BHP@2000RPM
 Motor (serial no.).....: HAZ00804
 Filter LIN suction side.....: 1 1/2" – 100 mesh washable strainer
 Signal to platform at.....: Fire alert, Gas alert, fault at gas/fire detector
 Air/Diesel shut down at.....:

- Overspeed of motor
- High exhaust temperature
- High coolant temperature
- Low oil pressure in motor
- Low air pressure
- Fire alert
- Gas alert
- Emergency stop
- Emergency stop from control room
- Low lubricate oil pressure pump

Power supply

Fuse (qty).....: 1 Fuse (A).....: 16
 El.Power1.....: 110-230 V 1 phase(Hz).....: 45/60 (kW).....: (A).....:

(Utility)

Flow / Pressure / Volume

Diesel Tank Volume (ltr).....:	500
Diesel consumption (ltr/hr).....:	120

Additional information

Equipment / Functions.....: Standard delivery is 10K (690 bar) / 3000 SCF/M. Possibility to Convert to 15K (1034 bar) 1,25" Cold End on request

- SafeGuard™ Novec 1230 fire extinguisher system,
- Fire extinguisher 12kg.
- OPS connections.